



# FUEL AND OIL DRAIN VALVE CROSS REFERENCE

CURTIS PART NO.	AUTO VALVE	SAF-AIR	MDI	AEROQUIP	DUKES
CCA-53		SA53S	F391-53S		
CCA-75	79C1	F75			
CCA-110H-4		CAV-110H-4			
CCA-160H-4		CAV-160H-4			
CCA-170H-4		CAV170H-4			
CCA-180H-4		CAV-180H-4			
CCA-1200	710C-4	SA5817-4C			
CCA-1800/CCA-110SS	BJ1000AS1MY	CAV-110			
CCA-1900/CCA-160SS	BJ1000AS1MX	CAV-160			
CCA-2000	1100B52Z	CAV-180			
CCA-2100	1100B52Z-G	CAV-170			
CCA-2500		SA18	F391-18		
CCA-2600		SA14	F391-14		
CCA-2700		SA32	F391-32		
CCA-2800		SA72	F391-72		
CCA-2900		SA82	F391-82		
CCA-2450		M12175			
CCA-2460		S5020J			
CCA-2474		RM12175			
CCB-5000		P5000			
CCB-6250		S6250			
CCB-32000		F62			
CCB-38000		F50			
CCA-38001		F50-180			
CCB-33000				AE99950G	
CCB-36000H				AE80664H	
CCA-641					367-00
CCA-642					1240-00-1

All applications sourced from available manuals. It is the responsibility of the installer to verify fit and function of all valve information supplied in this guide.



## TORQUE SPECIFICATIONS

STRAIGHT THREADS		SPECIAL THREAD W/CRUSH WASHER		PIPE THREADS	
3/8-24	80-85 In. Lbs.	12mm 1.75	80-85 In. Lbs.	1/8-27 NPT	40-45 In. Lbs.
7/16-20	80-85 In. Lbs.	1/20-20	60-70 In. Lbs.	1/4-18 NPT	80.85 In. Lbs.
1/2-20	80-85 In. Lbs.			3/8-18 NPT	105-115 In. Lbs.
9/16-18	80-85 In. Lbs.			1/2-14 NPT	155-165 In. Lbs.
3/4-16	80-90 In. Lbs.				
5/8-18	190-210 In. Lbs.				

### We recommend the following thread sealant

1. Pipe threads: 1/4" Teflon tape. Permatex 80632 thread sealant, Loctite 592 PST pipe sealant
2. Straight Threads: Lubricating Oil



CURTISVALVES.COM